

A. MECHANICAL(UNIT:mm)

RJ45 MECHANICAL NOTES:






REV	ECN NO	DESCRIPTION	DATE
A	/	New Drawing	2025/4/8

- 1.THE PRODUCT IS ROHS COMPLIANT.
- 2.ALL DIMENSIONS FOLLOW :
 - FCC SUBPART F, 68,500, FIGURE (C)(2)(I) & (C)(2)(II) & (C)(3)(I) IEC 60603-7
 - ALL PLUGS MUST BE MEETING THE REQUIREMENTS OF PLUG GO & NO-GO GAUGE.
- 3.GAUGE FOLLOW : FCC SUBPART F, 68,500, FIGURE (C)(4)(I) & (C)(5)(I)
 - THERE MUST BE NO DAMAGE TO HOUSING AND LOCKING LATCH.
 - THERE MUST BE NO NICKS AND CUTS IN CABLE.
 - DURABILITY : 750 CYCLES GENERALLY
- 4.PART CAN BE RECOMMENED FOR REFLOW SOLDERING PROCESS.
 - PEAK REFLOW SOLDERING TEMPERATURE IS 260°C MAX,10SECONDS MAX.
- 5.OPERATING TEMPERATURE:-40 TO +85°C;
- 6.STORAGE TEMPERATURE: -40 TO +85°C

7.MATERIAL:


- 7.1 HOUSING: HIGH TEMPERATURE THERMOPLASTIC LCP.
FLAMMABILITY RATING ,UL 94V-0; COLOR:BLACK.
- 7.2 SHELL: BRASS C2680H, THICKNESS=0.20mm.PLATING NICKEL 30u"Min;
- 7.3 RJ TERMINAL: HIGH TEMPERATURE THERMOPLASTIC LCP,COLOR:BLACK;
UL 94V-0;
RJ PIN:THICKNESS=0.30mm.PHOS-BRONZE C5210EH.
PLATING: 50u" MIN NICKEL UNDERPLATING ALL AREA.
100u" MIN TIN ON SOLDER TAIL.
6u" GOLD ON CONTACT AREA.
- 7.4 PHY PIN:THICKNESS=0.30mm. BRASS C2680EH.
PLATING: 50u" MIN NICKEL UNDERPLATING ALL AREA.
100u" MIN TIN ON SOLDER TAIL.
- 7.5 LIGHT PIPE : PC, TRANSPARENT

8.CODING PRINCIPLES



All dimensions follow :
FCC subpart F, 68,500, Figure (C)(2)(I)
IEC 60603-7

STANDARD MODULAR PLUG ASSEMBLY




RECOMMEND PLUG DIM


X. ± 0.40	APPD: LH.WANG	 思科飞尔技术(深圳)有限公司 SISCOFER TECHNOLOGY (SHENZHEN) CO.LTD
.X ± 0.30	CHKD: LOUIS	
.XX ± 0.25	DR: LIANG	PART NO: RN2-GA6B50GDBPR
.XXX ± 0.20		TITLE: 2X2 Port 10/100/1000BASE-T POE RJ45 JACK Magnetics
X* ± 3' .X* ± 2'		
UNITS: mm		
	SHEET: 1 OF 2	REV: DWG NO: REMARK:
	SCALE: 1:1	A RN2-0001 XXX-XXXX



B.SCHEMATICS



C:PIN ASSIGNMENT FOR PCB LAYOUT



D. ELECTRICAL SPECIFICATIONS @25℃ TRANSMITTER FILTER & RECEIVER FILTER

TYPE : BALANCE LOW PASS 100Ω IMPEDANCE

INSERTION LOSS : 1~125MHz -1.2dB MAX.

RETURN LOSS : 1~30MHz -18dB MIN. LOAD 100Ω
30~60MHz -16dB MIN. LOAD 100Ω
60~80MHz -12dB MIN. LOAD 100Ω
80~100MHz -10dB MIN. LOAD 100Ω

COMMON MODE REJECTION
@1~100 MHz -30dB MIN.

CROSS TALK
@ 1~100MHz -30dB MIN.


INDUCTANCE (OCL) @ 100KHz, 0.1V, 8mA DC BIAS 350 uH MIN.

DCR:1.2 OHM MAX


DC CURRENT/VOLTAGE RATING-POE:
720MA MAX @57VDC(CONTINUOUS)

HIPOT TEST
PHY SIDE(INPUT) TO CABLE SIDE(OUTPUT) : 1500Vrms 60S

E:LED SPECIFICATION



LEFT LED



RIGHT LED

Emitting Color	λp (nm)	Vf @If=20mA	Ir @Vr=5V
GREEN	570	1.7 ~2.6 V	10μA max
YELLOW	590	1.7 ~2.6 V	10μA max

X. ± 0.40	APPD:		思科飞尔技术（深圳）有限公司 SISCOFER TECHNOLOGY (SHENZHEN) CO.LTD			
.X ± 0.30	LH.WANG					
.XX ± 0.25	CHKD:	PART NO:	RN2—GA6B50GDBPR			
.XXX ± 0.20	LOUIS					
X* ± 3' .X* ± 2'	DR:	TITLE:	2X2 Port 10/100/1000BASE—T POE RJ45 JACK Magnetics			
UNITS: mm	LIANG					
	SHEET:	2 OF 2	REV:	DWG NO:	REMARK:	
	SCALE:	1:1	A	RN2—0001	XXX—XXXX	